

SMARTcare



[Abb. Typ 2 | fig. Type 2]

Bestell-Nr. | Part No.

SMARTcare 1	2003 1010
SMARTcare 2	2003 0740
SMARTcare 3	2003 1026

Maße (B x H x T)	280 x 345 x 300 mm	Dimensions (W x H x D)	280 x 345 x 300 mm
Gewicht	7,3 kg	Weight	7.3 kg
Nennspannung	100 - 230 V	Nominal voltage	100 - 230 V
Nennfrequenz	50/60 Hz	Nominal frequency	50/60 Hz
Nennleistung	max. 45 VA	Nominal power	max. 45 VA
Schutzklasse	I	Protection class	I
Schallpegel	60 (65) dB(A)	Sound pressure level	60 (65) dB(A)
Druckluft	4,5 - 6 bar	Compressed air	4.5 - 6 bar
Luftverbrauch	40 NI/min	Air consumption	40 NI/min
Druckluftqualität		Compressed air quality	
- Restölgehalt	max. 0,1 mg/m ³	- Residual oil content	max. 0.1 mg/m ³
- Reststaubgehalt	max. 1 µm, max. 0,1 mg ³	- Residual dust content	max. 1 µm, max. 0.1 mg ³
- Restwassergehalt	max. 0,1 g/m ³ bei -40 °C	- Residual water content	max. 0.1 g/m ³ at -40°C
Integrierte Kupplungen		ISO 3964 integrated couplings	
ISO 3964			
- SMARTcare Typ 1	1	- SMARTcare Type 1	1
- SMARTcare Typ 2	2	- SMARTcare Type 2	2
- SMARTcare Typ 3	3	- SMARTcare Type 3	3