

915



Steckertyp Connector type	915 Intercontec: ESTB202NN0044L053000
Crimpchse (Leistung/PE)	Leistung/PE Power / PE = Intercontec 60.251.11 Signal Sensor = Intercontec 60.252.11
Kabel Cable	Nexans Power PSL (4G1.0+(2x0.75))

Leiteraufbau Cable structure	(4G1.00mm²(2x0.75mm²))
Nennspannung Nominal Voltage	U ₀ /U = 600 / 1000 V
Prüfspannung EN50289-1-2 Test Voltage EN50289-1-2	Ader – Ader, 1min = 4 kV Wire – Wire, 1min = 4kV Ader – Schirm, 1min = 3 kV Wire – Shield, 1min = 3 kV
Mantelmaterial Outer jacket material	PUR
Außendurchmesser D Outer Diameter D	9,5 ± 0,3 mm
Min zul. Biegeradius (statisch) Min bending radius (static)	5 x D
Min zul. Biegeradius (permanent bewegt) Min bending radius (permanent bending)	10 x D

Belegung Steckverbinder Connector assignment		
Bezeichnung Name	Steckverbinder 915 – Spindel Connector 915 – Spindle	Verbindungskabel 915 Connecting cable 915
Phase U	A	U / 1
Phase V	B	V / 2
Phase W	C	W / 3
PE	⏏	GN / YE
PTC Temp. Sensor TP-	1	WH
PTC Temp. Sensor TP+	2	BK

